

ENERLYTE - Pure lead pos, thick plate - 20+ year batteries



Watts per cell to 1.90 volts per cell													
Model	Nominal volts	10 min	15 min	20 min	30 min	45 min	1 hr	2 hrs	3 hrs	4 hrs	5 hrs	8 hrs	10 hrs
6V57	6	64	61	58	52	45	40	27	21	19	16	12	10
6V85	6	96	92	87	78	67	60	40	32	28	24	18	15
6V115	6	128	123	116	104	89	80	53	43	37	32	24	20
2V225	2	255	245	231	208	179	159	107	85	74	64	47	39
2V250	2	287	276	260	234	201	179	120	96	83	72	53	44
2V310	2	351	337	318	286	246	219	147	117	102	87	65	54
2V360	2	408	392	370	332	286	255	171	137	119	102	75	63
2V400	2	485	466	440	395	340	303	204	166	144	125	93	80
2V500	2	546	525	495	444	383	341	230	187	161	140	104	90
2V550	2	606	583	550	493	425	378	255	208	179	156	116	100
2V605	2	667	641	605	543	468	416	281	228	197	172	127	110
2V660	2	727	700	660	592	511	454	306	249	215	187	139	120
2V715	2	764	734	704	632	545	492	332	270	233	203	150	130
2V930	2	735	718	658	569	522	481	392	322	264	233	172	144
2V1170	2	945	924	846	731	671	618	504	414	340	300	221	186
2V1690	2	1366	1334	1222	1056	969	893	727	597	491	434	319	268
2V2200	2	1786	1745	1598	1381	1268	1167	951	781	642	567	417	351
2V2400	2	1996	1950	1786	1544	1417	1305	1063	873	718	634	466	392
2V3400	2	2731	2669	2444	2112	1939	1785	1455	1195	982	867	638	536
2V2400©	2	2340	2273	2006	1766	1565	1428	1125	906	741	644	474	398
2V3400©	2	3202	3110	2744	2417	2141	1954	1540	1240	1014	881	649	544

@ These cells have copper inserted posts, which are recommended for applications where the required discharge autonomy is less than 1 hour

ENERLYTE - Pure lead pos, thick plate - 20+ year batteries



Watts per cell to 1.85 volts per cell													
Model	Nominal volts	10 min	15 min	20 min	30 min	45 min	1 hr	2 hrs	3 hrs	4 hrs	5 hrs	8 hrs	10 hrs
6V57	6	81	77	72	63	53	47	30	24	20	17	13	11
6V85	6	122	115	107	95	80	71	46	36	30	26	19	17
6V115	6	162	153	143	127	107	94	61	48	40	35	25	22
2V225	2	325	306	286	253	214	189	122	96	81	69	50	45
2V250	2	365	345	322	285	241	212	137	107	91	78	57	50
2V310	2	446	421	393	348	294	259	167	131	111	96	69	61
2V360	2	519	490	458	405	342	302	195	153	129	111	81	71
2V400	2	619	584	546	483	408	360	241	191	163	139	99	85
2V500	2	697	657	614	544	459	405	272	215	183	156	112	96
2V550	2	774	730	683	604	510	450	302	239	204	174	124	107
2V605	2	852	803	751	664	561	495	332	263	224	191	137	117
2V660	2	929	877	819	725	613	540	362	287	244	208	149	128
2V715	2	975	920	874	773	653	585	392	310	265	226	161	139
2V930	2	967	930	861	745	684	611	473	381	315	281	201	176
2V1170	2	1244	1196	1107	958	879	786	608	489	406	361	258	226
2V1690	2	1796	1727	1599	1384	1270	1135	879	707	586	522	373	327
2V2200	2	2349	2259	2091	1810	1660	1485	1149	925	766	682	488	427
2V2400	2	2625	2525	2338	2023	1856	1659	1284	1033	856	762	545	477
2V3400	2	3593	3455	3199	2769	2539	2271	1758	1414	1172	1043	746	653
2V2400©	2	3020	2880	2637	2319	2030	1814	1349	1073	885	776	555	485
2V3400©	2	4133	3941	3608	3173	2778	2483	1846	1469	1211	1062	759	664

@ These cells have copper inserted posts, which are recommended for applications where the required discharge autonomy is less than 1 hour

ENERLYTE - Pure lead pos, thick plate - 20+ year batteries



Watts per cell to 1.80 volts per cell													
Model	Nominal volts	10 min	15 min	20 min	30 min	45 min	1 hr	2 hrs	3 hrs	4 hrs	5 hrs	8 hrs	10 hrs
6V57	6	99	88	81	70	59	51	32	25	21	18	13	11
6V85	6	148	132	121	106	88	76	48	38	31	26	20	17
6V115	6	197	175	162	141	118	102	64	50	41	35	27	22
2V225	2	394	351	324	282	236	204	129	101	83	70	53	45
2V250	2	443	395	364	317	265	229	145	114	93	79	60	50
2V310	2	542	483	445	387	324	280	177	139	114	97	73	62
2V360	2	631	562	518	450	377	326	206	162	132	112	85	72
2V400	2	759	676	623	542	454	391	259	205	173	147	106	88
2V500	2	854	760	701	610	511	440	291	231	195	166	119	99
2V550	2	949	845	779	677	568	489	324	256	216	184	132	110
2V605	2	1044	929	857	745	624	538	356	282	238	203	146	121
2V660	2	1139	1013	935	813	681	587	388	307	259	221	159	132
2V715	2	1196	1064	997	867	727	636	421	333	281	240	172	143
2V930	2	1254	1166	1064	928	817	727	534	415	349	302	210	186
2V1170	2	1612	1500	1368	1193	1051	935	686	534	449	388	270	239
2V1690	2	2329	2166	1977	1723	1518	1351	991	772	648	560	390	345
2V2200	2	3045	2833	2585	2254	1985	1766	1296	1009	848	733	510	451
2V2400	2	3403	3166	2889	2519	2218	1974	1449	1128	948	819	570	504
2V3400	2	4657	4332	3953	3447	3035	2701	1983	1543	1297	1121	780	689
2V2400©	2	3868	3614	3091	2631	2303	2035	1497	1159	968	836	580	510
2V3400©	2	5292	4946	4230	3601	3152	2785	2049	1587	1325	1144	793	697

© These cells have copper inserted posts, which are recommended for applications where the required discharge autonomy is less than 1 hour

ENERLYTE - Pure lead pos, thick plate - 20+ year batteries



Watts per cell to 1.75 volts per cell													
Model	Nominal volts	10 min	15 min	20 min	30 min	45 min	1 hr	2 hrs	3 hrs	4 hrs	5 hrs	8 hrs	10 hrs
6V57	6	108	96	87	74	61	52	34	27	22	19	14	11
6V85	6	162	144	130	112	92	79	51	40	34	29	20	17
6V115	6	216	192	174	149	123	105	68	53	45	38	27	23
2V225	2	433	384	348	298	245	210	135	106	90	77	54	45
2V250	2	487	432	391	335	276	236	152	119	101	86	61	51
2V310	2	595	528	478	410	338	288	186	146	123	106	75	62
2V360	2	692	614	556	477	393	336	216	170	144	123	87	72
2V400	2	889	789	715	612	505	431	273	214	183	156	109	91
2V500	2	1001	888	804	689	568	485	307	241	205	175	123	102
2V550	2	1112	986	893	765	631	539	341	268	228	195	137	113
2V605	2	1223	1085	983	842	694	593	375	295	251	214	150	125
2V660	2	1306	1169	1059	919	757	647	409	321	274	234	164	136
2V715	2	1345	1213	1112	972	804	696	440	346	295	252	177	146
2V930	2	1469	1413	1264	1054	931	791	570	448	375	321	223	191
2V1170	2	1889	1816	1625	1355	1198	1017	733	576	483	413	287	246
2V1690	2	2728	2623	2347	1957	1730	1469	1058	832	697	596	415	355
2V2200	2	3567	3430	3069	2559	2262	1921	1384	1088	912	780	542	464
2V2400	2	3987	3834	3430	2860	2528	2147	1547	1216	1019	871	606	518
2V3400	2	5456	5247	4694	3914	3460	2938	2116	1665	1395	1192	829	709
2V2400©	2	4361	4176	3602	3038	2631	2272	1600	1252	1043	888	614	522
2V3400©	2	5968	5715	4929	4157	3601	3110	2190	1713	1428	1216	840	715

@ These cells have copper inserted posts, which are recommended for applications where the required discharge autonomy is less than 1 hour

ENERLYTE - Pure lead pos, thick plate - 20+ year batteries



Watts per cell to 1.70 volts per cell													
Model	Nominal volts	10 min	15 min	20 min	30 min	45 min	1 hr	2 hrs	3 hrs	4 hrs	5 hrs	8 hrs	10 hrs
6V57	6	120	105	94	79	64	54	33	26	23	20	14	11
6V85	6	180	157	141	119	96	80	50	39	35	30	21	17
6V115	6	241	210	189	158	127	107	67	52	47	39	27	23
2V225	2	481	420	377	317	255	214	134	104	93	79	55	46
2V250	2	541	472	424	356	287	241	150	117	105	89	62	51
2V310	2	662	577	518	436	350	294	184	143	128	109	75	63
2V360	2	770	672	603	507	408	342	214	167	149	126	88	73
2V400	2	980	854	766	643	518	438	275	218	186	158	110	91
2V500	2	1103	961	862	723	583	493	310	245	209	178	124	103
2V550	2	1225	1067	958	804	648	547	344	272	233	197	138	114
2V605	2	1348	1174	1053	884	713	602	378	300	256	217	152	125
2V660	2	1458	1270	1140	956	771	651	409	324	277	235	164	136
2V715	2	1482	1313	1192	1021	826	701	440	350	299	254	177	146
2V930	2	1547	1467	1317	1107	979	834	601	466	386	334	230	191
2V1170	2	1989	1886	1693	1423	1259	1072	772	599	496	429	295	246
2V1690	2	2874	2725	2446	2056	1818	1549	1116	865	716	620	427	355
2V2200	2	3758	3563	3198	2688	2377	2026	1459	1131	937	811	558	464
2V2400	2	4200	3983	3574	3005	2657	2264	1631	1264	1047	906	624	519
2V3400	2	5747	5450	4891	4112	3636	3098	2231	1730	1433	1240	853	710
2V2400©	2	4585	4319	3713	3168	2776	2348	1698	1306	1070	921	633	521
2V3400©	2	6274	5910	5081	4334	3798	3213	2324	1788	1464	1261	866	712

@ These cells have copper inserted posts, which are recommended for applications where the required discharge autonomy is less than 1 hour

ENERLYTE - Pure lead pos, thick plate - 20+ year batteries



Watts per cell to 1.65 volts per cell													
Model	Nominal volts	10 min	15 min	20 min	30 min	45 min	1 hr	2 hrs	3 hrs	4 hrs	5 hrs	8 hrs	10 hrs
6V57	6	135	117	104	85	68	56	35	27	23	20	14	11
6V85	6	202	176	155	128	102	84	52	41	35	29	20	17
6V115	6	269	235	207	170	135	113	70	55	46	39	27	22
2V225	2	539	470	414	341	271	225	140	109	93	78	54	45
2V250	2	606	529	466	384	305	253	157	123	104	88	61	50
2V310	2	741	646	570	469	372	310	192	150	128	107	75	62
2V360	2	862	752	663	545	433	360	224	175	148	125	87	72
2V400	2	1071	934	824	678	538	447	278	218	185	156	109	90
2V500	2	1204	1051	927	762	606	503	312	245	208	175	123	101
2V550	2	1338	1168	1030	847	673	559	347	273	231	195	136	112
2V605	2	1472	1284	1133	932	740	615	382	300	254	214	150	123
2V660	2	1572	1378	1210	995	791	666	413	323	274	231	161	134
2V715	2	1606	1413	1246	1042	834	710	441	346	295	249	174	142
2V930	2	1600	1494	1341	1128	1005	857	616	476	390	334	230	190
2V1170	2	2057	1920	1724	1450	1292	1102	792	612	501	429	295	244
2V1690	2	2972	2774	2491	2095	1866	1591	1144	884	724	620	426	353
2V2200	2	3886	3627	3257	2740	2440	2081	1497	1156	947	811	558	462
2V2400	2	4343	4054	3640	3062	2727	2326	1673	1292	1058	907	623	516
2V3400	2	5943	5548	4981	4190	3732	3183	2289	1768	1448	1240	853	706
2V2400©	2	4713	4367	3780	3221	2835	2407	1738	1336	1082	919	631	518
2V3400©	2	6449	5976	5173	4408	3879	3294	2378	1828	1481	1258	863	709

@ These cells have copper inserted posts, which are recommended for applications where the required discharge autonomy is less than 1 hour